



> SCAN

fi-7160

A4 DOCUMENT SCANNER

BECAUSE RESULTS MATTER



- > Equipped with Intelligent Sonic Paper Protection that detect irregular paper noise
- > A4 portrait at 300 dpi; 60ppm/120ipm, scan mixed batches up to 80 sheets
- > Skew reducer - Independent pick rollers ensure a skewed document will not affect the alignment of following sheets
- > Integrated LCD and Scanner Central Admin for hassle free monitoring and administration
- > PaperStream IP and PaperStream Capture; Fujitsu developed scanner driver and image capturing software
- > Small footprint and robust design

The fi-7160 is easy to set up, use and maintain and comes bundled with a user friendly and intuitive scanner driver, PaperStream IP, for high quality image processing, along with batch scanning automation and enhancement software PaperStream Capture. A4 portrait scanning speeds in both colour or black and white at up to 300 dpi is 60 pages per minute or 120 images per minute through the 80 page capacity Automatic Document Feeder (ADF).

HASSLE FREE MONITORING AND ADMINISTERING

The fi-7160 comes with Scanner Central Admin tools, including functions that system administrators can use to manage the installation and operation of multiple scanners, monitor operation status and update drivers and software from one location. This ability dramatically reduces the cost and work that goes into setting up, operating and maintaining many scanners in an organisation and also in expanding the scanner network to multiple locations.

TECHNICAL SPECIFICATIONS

Scanner type: ADF (Automatic Document Feeder)

Scanning modes: Colour / Greyscale / Black and White / Automatic Detection

Image sensor: Colour CCD x 2

Light source: White LED array x 2 (front x 1, back x 1)

Optical Resolution: 600 dpi

Scanning speed: (A4 portrait): 60 ppm /120 ipm (200 and 300 dpi)

ADF capacity – 80 sheets

Document size/Document weight: Min: 52 x 74 mm; Max: 210 x 297 mm / 27 to 413g/m²

Interface: USB 3.0 (USB 2.0 compatible)

Driver: PaperStream IP

Power requirement: AC 100V to 240V,

Operation environment: Temperature: 5°C to 35°C, Relative humidity: 20 to 80% (non-condensing)

Power consumption: Operating: 38W or less; Sleep mode: 1.8W or less

Dimensions (W x D x H):300 x 170 x 163 mm

Device weight: 4.2kg

Environmental compliance: ENERGY STAR® compliant/RoHS/Ecodesign

Compatibility: Windows 8, 7, Vista, XP, Server 2012, Server 2008

FOR MORE INFORMATION ABOUT **fi-7160**, PLEASE VISIT

www.kyoceradocumentsolutions.co.uk

KYOCERA Document Solutions (UK) Ltd, Eldon Court, 75-77 London Road, Reading RG1 5BS

Tel: 0118 931 1500, Fax: 0118 931 1108

www.kyoceradocumentsolutions.co.uk, info@duk.kyocera.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.